

METHOD AND APPARATUS FOR SCHEDULING INVALIDATION TESTS FOR HTTP SESSIONS

Field of the Invention

The invention pertains to hypertext transfer protocol (HTTP) and the World Wide Web (the Web). More particularly, the invention pertains to maintenance of http session data at the server side, and most particularly, to invalidation of session data when sessions time out.

Background of the Invention

By now, almost everyone is familiar with the Internet and the World Wide Web (the Web). The Internet is a collection of interconnected communication networks that span the globe. Information content on the Internet is presented via pages, each page comprising a file that is stored on (or dynamically built by) a computer server that is coupled to the Internet and assigned a Uniform Resource Locator (URL), which is essentially an address on the Internet.

Web browsers are computer programs that enable one to access and view Web pages via direct addressing (typing the address of a Web page in an address field of the browser) and/or by hyperlinking, as is well known in the art. Netscape Navigator and Microsoft Explorer are two of the most common Web browsers in use today.

Hypertext transfer protocol (http) is the protocol used for transferring Web pages over the Internet. Servers are computers that form part of the Web and whose general

purpose is to provide (or serve) information to other computers coupled to the Web. Those computers that are used to request and receive information via the Web from http servers are typically termed client machines or client computers.

On the Web, information is served in the form of Web pages written in HTML (HyperText Markup Language). Thus, for example, a retail Web site operator couples to the Internet via one or more http servers on which are stored a plurality of Web pages written in HTML programming language. In actuality, many Web pages are not actually stored in Web page format, but are dynamically constructed upon receipt of a request for the page.

The HTML code defines the manner of presentation of information on the client machine. The HTML code also typically includes the textual content of the page. Other types of content, such as images, audio, background, and multimedia are contained in separate, supplemental, files stored in the server which are referenced within the HTML code by HTML tags.

In a common example, a customer accesses a Web retailer's Web site from a desktop computer using a Web browser. The customer's desktop computer utilizing the Web browser software would be considered a client machine.

The Web browser requests a particular Web page using http in a manner well known to those of skill in the art. Upon receipt of the request for a particular Web page, the server system corresponding to the URL of the requested page serves the HTML code for that page to the client machine via the Internet.

Http is a connectionless transfer protocol. This means that each request for a

Web page transmitted from a client to a server is completely freestanding and contains no information that relates that request to any other request. Thus, http itself has no provision for state information that would allow a server (or a client) to maintain historical information about a series of related http requests (e.g., consecutive requests for pages from a single Web site by a single client).

In many types of communication sessions between a particular client and a particular Web site, it may be desirable to associate http requests from a single client and maintain state information. For instance, at retail Web sites which, commonly use dynamically generated shopping cart pages to keep track of items being purchased by a particular client, maintaining state information is a necessity in order to keep track of the various products being added to the shopping cart by the user contained in different http requests. Countless other examples also exist. The term session will be used in this specification to refer to any group of requests for data from a network server system that one may wish to associate with each other. Typically, however, a session comprises requests from a single client machine to a single server system that are within a certain time period of each other. The concept of sessions is not limited to use on the Internet and http, but can be applied to any communication network using any protocol.

Accordingly, ways have been developed outside of the http protocol itself for maintaining such state (or session) information. One of the earliest ways developed for doing this was the use of cookies. Cookies are small pieces of data that a server sends to a client machine and that the client's Web browser knows to store in a

designated cookie folder or in browser memory. Thereafter, when that client sends a http request for a Web page to that server, the client's Web browser software sends the cookies associated with that URL to the server. The cookie might contain any particular information that the Web site operator feels the need to have in order to better service its customers. As an example, many Web sites allow individual clients to customize Web pages, such as a daily, electronic, newspaper containing only those articles that meet certain criteria selected by the customer and which criteria are stored as part of a cookie. Cookies are a common way to allow the Web site operator to identify the particular client making a request so that the operator can then pull up the appropriate information associated with that client and deliver the customized Web page. Persons of skill in these arts will recognize that other mechanisms for storing state data and the like are known and used in the field. However, the use of cookies is probably the most ubiquitous of the various mechanism in use today.

The `Javax.servlet.http.HttpSession` object in the Java programming language (commonly called `HttpSession`) is a newer way of maintaining state information at the server side. The `Javax.servlet.http.HttpSession` object builds on cookies as well as some of the other means of tracking state data in a layer on top of the http layer. `HttpSession` is a portion of a Java servlet API (Application Program Interface). Java is a programming language developed by Sun Microsystems, Inc. expressly for use in the distributed environment of the Internet. It can be used to create complete applications that may run on a single computer or be distributed among servers and clients in a network. It can be used to build small application modules, known as applets, for use

as part of a Web page. Applets make it possible for a Web page user to interact with a page. Applets are small programs that can be delivered to a Web browser as part of an HTML page. Web browsers that include a Java Virtual Machine (JVM) can run Java applets. The applet can execute at the client side to provide dynamic content and/or allow for interactivity. For example, a Java applet can allow a user at a client machine enter data onto a form. Applets thus allow for dynamic Web pages and interaction between the user at the client machine and the downloaded Web page. Java and Java applets are platform independent.

An API is a specific method prescribed by a computer operating system or by another application program by which a programmer writing an application program can make requests of the operating system or other application.

A Java servlet essentially is a server-side equivalent of an applet. A Java servlet API provides Web developers with a simple, consistent, mechanism for extending the functionality of an http server and for accessing existing business systems, i.e., the application program with which the HTML code interfaces. Servlets are server and platform independent. HttpSession essentially is an object of a Java servlet API that accumulates state data. It is built using cookies (and/or other existing state data tracking techniques) and associates http requests with those cookies (and/or the particular data pieces used in other data tracking techniques).

For further information concerning HttpSession, Java servlet APIs and the other matters discussed above, reference can be made to the servlet 2.2 (or later) specification.

It is common for high traffic Web sites to divide the tasks of servicing requests in to a three tier system with a different server or plurality of servers to handle each tier. The first, front end tier is the http server that processes the http aspects of a transaction. The second tier is termed the application server. The application server handles the content specific processing for the transactions. For instance, in a retail Web site, the application server would process the actual data for a purchase, such as creating an invoice, creating a bill of lading, checking inventory to determine if the ordered item is in stock, checking the customer's credit card information and confirming sufficient funds, record keeping, etc. The third tier comprises database servers that store the data needed to process requests. Such databases may include, for instance, a database of inventory and a database storing the content that is used to dynamically build Web pages. Within each tier, a large volume Web site server system may have multiple, redundant, servers. Particularly, any given server can only service so many requests in a given period. If the Web site expects more traffic than a single server can handle, it simply maintains multiple servers which can serve the same content. In such situations, since http is a connectionless protocol, one request from a particular client can be directed to one application server while the next request from the same client machine might be directed to a different application server. Accordingly, a means must be provided for the various servers to access the session data developed by another, redundant server.

A common way of enabling such sharing of http session data is by use of a database server that is accessible to the plurality of application servers for storing

session data. Particularly, an application server will store session data in local memory, but will also write a copy of the session data to the session database. If a different server services a request from a client, that different server can go to the database and read out the session data for the corresponding session.

5 Typically, the session data is updated in both the local memory and the database each time a request causes a change in the data. Particularly, the server updates the http session data in its local memory and also writes that data to the database after each request. Another method that has been used is herein termed manual update. With manual update, the servlet operator can explicitly, within the code, direct the server to write its locally stored session data to the database.

10 Eventually, all sessions end. For instance, the individual at the client side finishes his or her business with the Web site and either goes on visit another Web site or turns off his or her computer. The session data being maintained therefore must be invalidated at some point since it is stale data that is no longer of any value. The appropriate server-side application program may expressly make a determination as to when a session has ended. For example, a retail Web site might deem a session to have ended after a consumer checks out (and all of the business data processing needed to process the order has been completed). The appropriate application program may then expressly invalidate the session data stored in the database (among many other tasks not pertinent to the present invention that may be performed upon the closing of a session). Another common way for a session to end is for it to time out. Specifically, typically, the http server of the application server maintains a record of the

15

20

time of the last http request in a session and, if period since the last request exceeds a particular threshold (herein termed the time out interval), the session is closed. At a minimum this would involve invalidating the session data in the local memory and the database and may also involve other tasks.

5 Traditionally, while the servers are up and running (e.g., processing http requests from client machines and writing to and reading from the http session database), invalidation testing of the session data in the session database is run in parallel. Particularly, at specified intervals, an invalidation test program wakes up and polls all of the sessions stored in the session database to determine if they have timed out. For instance, the invalidation test simply may entail, for each session stored in the database, reading the last access time and the time out interval (either or both of which may be an attribute comprising the session data itself), and compare the time out interval to the difference between the last access time and the current time. If the time out interval is shorter than that difference, the session has timed out and the test
10 program invalidates the corresponding session data in the database.

15 The invalidation test for each session can involve at least one read from the session database and, if the session needs to be invalidated, at least one write (to flag the session data as invalid or delete it outright). Thus, invalidation testing entails a substantial amount of traffic at the database and substantially increases the load on the
20 database. The additional traffic created by the invalidation testing of the session database can be particularly taxing on the system during those times of day when there already is high traffic in the server system due to a large volume of client machines

accessing the server system.

Writing to the database is a particularly expensive process in terms of consumption of processing power and time. Accordingly, it is desirable to reduce the number of writes to a session database in order to conserve system resources.

It is an object of the present invention to provide an improved method and apparatus for invalidating http session data in a back-end database.

It is another object of the present invention to provide a method and apparatus for invalidating http session data in a back-end database that minimizes database traffic.

Further, it is an object of the present invention to provide a method and apparatus to avoid invalidating http session data in a back-end database during periods of high traffic.

SUMMARY OF THE INVENTION

The invention is a method and apparatus for invalidating session data stored in a database. In accordance with the invention, no real time testing for session time out and invalidation of session data for http sessions in the database is performed. Instead, the session data for timed out sessions remains in the database until a specified time. Preferably, the local copy of the http session data is still tested for time out and invalidation.

In at least one preferred embodiment of the invention, the specified time is a time when database traffic is expected to be minimal in order to minimize the possibility

that the extra traffic load on the database server inherent in invalidation testing does not overstrain the system. In at least one preferred embodiment of the invention, at that specified time, all http sessions are invalidated without actually testing them for time out. Many Web site operators may be willing to accept the possibility that some sessions may not have timed out and that useful session data may be lost in exchange for the substantial decrease in database server load since this scheme could enable the Web site operator to design a much less expensive server system because the maximum load that the database must be designed to handle would be substantially lessened.

In an alternate embodiment of the invention, at the specified time, each session can be individually tested for time out and only those sessions which have actually timed out invalidated.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram showing a network architecture including a server system in accordance with the present invention.

Figure 2 is a flow chart disclosing http session invalidation in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 is a block diagram of a communication network system architecture

including a server system according to a preferred embodiment of the present invention. The invention will herein be described in connection with the Internet and http. However, it will be understood by those of skill and the art that the invention is applicable to any type of distributed communication network in which copies of session data are maintained in a shared database in any manner. Further, while the invention is particularly adapted and suitable for use in connection with session data maintained in the form of HttpSession objects of Java servlet APIs in J2EE (Java™2 Platform, Enterprise Edition) it can be applied to any manner of maintaining state data for a communication session on a distributed network. Information on J2EE can be obtained from Sun Microsystems, Inc. of Palo Alto, California, USA.

Referring to Figure 1, as previously noted, the Internet 11 essentially is a distributed communication network that spans the globe. A Web site operator operating a server system 12 couples to the Internet 11 through one or more http servers 13. The http server is coupled to one or more application servers 14₁, 14₂, ..., 14_n. Each application server 14₁-14_n is essentially redundant of the other application servers and is capable of serving the same content and performing the same processing tasks. In addition, the server system may include a database server 18 for storing content accessible to the application servers that may be necessary for processing the http requests.

For instance, in connection with a retail Web site that sells goods via the Internet, the http server(s) 13 handle all tasks relating to interfacing to the clients via the Internet using http, ftp, etc.. The application server(s) 14 handle application

processing tasks such as creating a purchase order, creating an invoice, checking stock to determine if a requested product is available, creating a shipping order, calculating tax and shipping charges, adding such charges to the price of the item being purchased, checking the validity of a credit card number used to charge for the purchase, etc. The application server(s) 14 access necessary data for performing these tasks, such as inventory data, shipping data, etc. from the database server(s) 18. The http server(s) 13 interface with the application server(s) 14 using tools such as Java servlet APIs.

In the case of a Web site that dynamically creates Web pages responsive to requests (rather than simply storing pages), the application server(s) would also perform the tasks of dynamically creating the Web pages using data stored in databases maintained in the database server(s).

An individual wishing to view Web pages via the Internet runs Web browser software on his or her computer or client machine 16. Web browsers are capable of communicating using http, ftp and other protocols. A client Web browser can issue http requests via the Internet to any particular server system for content to be presented to it in the form in HTML pages. When a server system 13 receives such a request, it returns the requested HTML page to the requesting client and creates http session data for the session. Although there are other options, in one option, Web site operators who wish to maintain session information operate Java-enabled application servers capable of running Java servlet API's, and utilize the HttpSession object to maintain the session data.

As previously mentioned, when there are multiple, redundant, application servers 14, it is possible, if not likely, that requests in a single http session may be serviced by different application servers. Accordingly, the various servers must be able to obtain the session data (e.g., the HttpSession object) for a given session that may have had previous requests serviced by a different one of the application servers. Accordingly, one of the databases maintained in the database server 18 is a session database. Data for http session handled by any of the server, $14_1 - 14_n$, is stored in the session database. Thus, when an application server handles an http request in connection with a particular session for which that server does not have a local copy of the corresponding session data (for example, because it has not serviced any of the previous requests pertaining to that session), it can go to the session database to read out the session data that was written to the database by the server that processed the previous requests in that session.

Accordingly, each server maintains a copy of the session data for each of the http sessions that it is servicing in a local memory and also writes a copy of the session data to the http session database 18. If a server switch occurs for a given session, the new server can go to the database and request the session data pertaining to that session.

In accordance with the present invention, invalidation testing of the session data stored in the database is not performed on a routine or regular basis in parallel with the processing of http requests. (Testing is still performed with respect to the locally stored copies of the http session data). Instead, in at least one preferred embodiment of the

invention, all of the http sessions in the http session database are tested at one time. Preferably, that time is during a period that the traffic at the Web site is relatively low, e.g., 3:00 am in the morning. In certain embodiments, the time can be a particular time of day. In other embodiments, a process can be run periodically to determine the load on the server system or the load on the session database, and when it falls below a predetermined threshold, the session invalidation process can be run only if the load is below a certain threshold.

In one particularly preferred embodiment, at the designated time, the process simply wipes out the entire database without performing any invalidation testing. Many Web site operators may be willing to accept the possibility of losing valid and useful session data in order to have a more efficient system. For those Web site operators that are not willing to make that sacrifice, each session can be individually tested for time out at the designated time and only those that are determined to have timed out are invalidated.

Figure 2 is a flow chart illustrating an overall session invalidation scheme in accordance with the present invention.

The process starts at step 201 when it is the designated time. In this particular example, the designated time is a particular time of day, namely, 3:00am. However, as previously noted, the time can be dynamically controlled to be a time when it is dynamically determined that the load on the server system is low. In step 203, the process selects one of the sessions that has not been tested yet. In step 205, it runs an invalidation test to determine if the session has timed out. If it has, flow proceeds to

step 207 and the session data is invalidated in the database. There are many possible schemes for invalidating session data that would be well within the skill of persons in this art. One scheme would involve including a one bit valid flag as one of the attributes of the session data and resetting that flag to indicate that the session data is invalid and should not be used. Alternately, the data for the specific session is removed from the database. Then flow proceeds to step 209.

If the session has not timed out, then flow proceeds directly from 205 to step 209. In step 209, the system determines if all of the sessions in the database have been tested. If they have, the process ends at step 211. If they have not, then flow proceeds back to step 203 to flow through the test steps repeatedly until all the sessions have been tested for a time out.

As previously noted, in other embodiments of the invention, the system may simply wipe out all existing sessions in the http database without testing them, if the Web site operator is willing to accept the potential loss of data that can occur if a session that has not timed out is invalidated.

It should be borne in mind that every time a request is received for http session data, a time out invalidation test is performed. This essentially is a process that occurs independent of the present invention. Obviously, if a session has timed out, the database should not return the session data in response to the request. However, there is modification to that process in accordance with the present invention. Accordingly, Figure 2 also illustrates the process of invalidation testing of a session in response to a request for the corresponding session data in what is essentially a

parallel path (comprising steps 220, 222, 224, 226, 228, and 230).

The process starts at step 220 when a new request for session data from the session database is received. In step 222, it is determined whether the requested session has timed out. If not, flow proceeds to step 224, where the session data is returned to the requesting Java Virtual Machine. If the session has timed out, flow instead proceeds from step 222 to step 226. In step 226, the database informs the requesting JVM that the session has timed out and removes the session data from the database (or otherwise invalidates it).

In an alternate embodiment of the invention, the session data stored in the database is not touched at this time and, instead, it will be invalidated at the designated time in accordance with the present invention. Accordingly, one or more writes to the database that would normally be necessary to invalidate the session data at this time would not be performed.

Flow proceeds from step 226 to step 228 in which the server running the JVM that requested the timed out data creates new session data and writes it to the database as a new session to be added to the database.

In accordance of the present invention, the large number of reads and writes to and from the session database server that would normally be carried out in connection with invalidation testing of sessions in parallel with the regular processing of http requests is minimized or completely eliminated. This reduces the load on the server system and particularly on the http session database.

Having thus described a few particular embodiments of the invention, various

alterations, modifications, and improvements will readily occur to those skilled in the art. Such alterations, modifications and improvements as are made obvious by this disclosure are intended to be part of this description though not expressly stated herein, and are intended to be within the spirit and scope of the invention. Accordingly, the foregoing description is by way of example only, and not limiting. The invention is limited only as defined in the following claims and equivalents thereto.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000